

Reference Documentation

May 24, 2007

Contents

1	Class List	1
2	Class Hierachy	1
3	Globals	1

Abstract

Reference Documentation.

Generated: ghaase on mephisto, Thu May 24 08:44:59 2007..

1	Class List	
2	Class Hierachy	
3	Globals	

Index by file

bsp_20_fkt.hpp

- double **riemann** (double (* const func)(double), const double &a, const double &b, const int n) 1
- double **derivative** (double (* const func)(double), const double &x, const double &h) 2
- double **riemann** (double (* const func)(double), const double &a, const double &b, const double eps=1e-4) 2
- double **derivative2** (double (* const func)(double), const double &x, const double eps=1e-4) 2
- double **newton_diff_approx** (double (* const func)(double), const double &a, const double &b, const double eps=1e-4) 2

Detailed Description

double **riemann** (double (* const func)(double), const double &a, const double &b, const int n) []

#include <bsp_20_fkt.hpp>

Calculates the integral value.of a 1D-function by the Riemann formula

Parameters:

func function func(x) to integrate

a	interval $[a,b]$
b	interval $[a,b]$
n	number of subintervals of $[a,b]$

Return:

integral $f(x)$ from a to b

```
double derivative ( double (* const func)(double), const double &x, const double &h) []
```

```
#include <bsp_20_fkt.hpp>
```

Calculates the first derivative $f'(x)$ of a 1D-function by the finite difference.

Parameters:

$func$	function $func(x)$ to differentiate
x	point for evaluation
h	distance from x in the finite difference formula

Return:

$f'(x)$

```
double riemann ( double (* const func)(double), const double &a, const double &b, const double
eps=1e-4) []
```

```
#include <bsp_20_fkt.hpp>
```

Calculates the integral value of a 1D-function for a given accuracy by the Riemann formula

Parameters:

$func$	function $func(x)$ to integrate
a	interval $[a,b]$
b	interval $[a,b]$
eps	absolute numerical accuracy

Return:

integral $f(x)$ from a to b

```
double derivative2 ( double (* const func)(double), const double &x, const double eps=1e-4) []
```

```
#include <bsp_20_fkt.hpp>
```

Calculates the first derivative $f'(x)$ of a 1D-function with a given accuracy by the finite difference.

Parameters:

$func$	function $func(x)$ to differentiate
x	point for evaluation
eps	absolute numerical accuracy

Return:

$f'(x)$

```
double newton_diff_approx ( double (* const func)(double), const double &a, const double &b,  
const double eps=1e-4) []
```

```
#include <bsp_20_fkt.hpp>
```

Solves the equation $f(x)=0$ in the interval $[a,b]$ with the Newton iteration using the finite difference to approximate the needed first derivative. Calculates the first derivative $f'(x)$ of a 1D-function with a given accuracy by the finite difference.

Parameters:

<i>func</i>	1D-function $\text{func}(x)$
<i>a</i>	interval $[a,b]$
<i>b</i>	interval $[a,b]$
<i>eps</i>	absolute numerical accuracy

Return:

one root of $\text{func}(x)$ in the given interval