Advanced Iterative Solvers and Optimization[1].

1 Introduction

Some 20 kilometers away from Linz the industrial company ENGEL Maschinenbau GesmbH in the field of mechanical engineering is situated. One of their fields is constructing and fabricating industrial machine components for injection moulding machines. The classical construction is based on bars, but ENGEL Maschinenbau holds a patent for the barless construction. The mass of the frame of a mid range injection moulding machine amounts to 4 tons, hence limits on transportation facilities hamper marketing of these machine components.

The following statements are correct for construction in lines of products, but they became more and more important for construction in single units also:

- An industrial machine component has to meet certain requirements.
- Due to lack of time the mechanical engineer who designs the industrial machine component has to stop his designing process after two or three drafts and take the best draft obtained so far.
- There is no more time left for more drafts that would either meet the requirements to a larger extent or be constructed more cheaply.

Becoming aware of these facts leads ultimately to the use of mathematics, resp. optimization, in industry, and, as a first step, to

2 The modelling

The frame of an injection moulding machine is briefly described by its 2D-cut given in figure 1.



Figure 1: Initial grid of the original shape (197 elements).

Typical dimensions are:

- thickness of one plate : 180 mm
- mass of one plate: 3.8 tons
- clumping force : 300 tons (line force)
- length / height : 2.8 m / 1.7 m
- 2 supporting points (areas)

Our first goal is to minimize the mass of the frame of the injection moulding machine subject to certain requirements (not all of them are constraints in the classical nomenclature of optimization), namely

- maximal von Mises stress : $\sigma_{\max}$
- maximal tensile stress: $\tau_{\max}$
- shrinking angle of clumping unit (vertical edges on top, called *wings*): $\alpha_{\max}$
- handling of the machine, feeding mechanism
- easy manufacturing

where the boundary of the cross section is described by parts of arcs and straight lines. Hence, we use 2D coordinates of corner points and their radii of curvature as design variables, i.e., $(x_i, y_i, r_i) =: v_{D,i}$.

$$\begin{aligned} -\mu\Delta\mathbf{u} - (\lambda+\mu)\nabla \mathrm{div}\mathbf{u} &= b \quad \text{in } \Omega \\ &+ B.C. \end{aligned} \tag{1}$$

$$\lambda = \frac{E\nu}{(1+\nu)(1-\nu)} \qquad \mu = \frac{E}{2(1+\nu)}$$

with λ, μ Lamé's elasticity constants
E modulus of elasticity
ν Poisson's ratio.

[1]This work has been partially granted by the *Forschungsförderung der Allgemeinen Sparkasse Oberösterreich*

This PDE governs the following shape optimization problem :

Minimize $\mathcal{F}(\mathbf{u}(v_D), v_D)$ with respect to $v_D := (v_{D,1}, \ldots, v_{D,N})$
taking into account the constraints

$$\begin{aligned} \sigma(x) &\leq \sigma_{\max} \qquad \forall x \in \Omega(v_D) \\ \alpha(\text{wings}) &\leq \alpha_{\max} \\ \tau(x) &\leq \tau_{\max} \end{aligned}$$

admissible geometry $\Omega(v_D) \iff$ box constraints on v_D .

Here, $\mathbf{u}$ is the (discrete) solution of the linear elasticity equations.

Most requirements are not really constraints, e.g., a larger angle will be acceptable if the mass decreases significantly. Hence, all requirements but the geometrical constraints on the design variables themselves are put into the objective

$$\begin{aligned} &\mathcal{F}(v_D, \mathbf{u}(v_D), \sigma, \alpha) \qquad (2) \\ &= w_m \cdot \text{mass}(v_D)/\text{m}_0 \\ &\quad + w_\sigma \cdot \sum \{\max(\sigma(x(v_i))/\sigma_{\max} - 1, 0)\}^2 \\ &\quad + w_{\alpha,m} \cdot (\alpha(\text{wings})/\alpha_{\max} - 1, 0)^2 \\ &\quad + w_{\alpha,s} \cdot (\alpha(\text{wings})/\alpha_{\text{soft}} - 1, 0)^2 \end{aligned}$$

w_m, $w_{\alpha,w}$, $w_{\alpha,s}$, w_σ are the weights of relevance of a criteria for the engineer.

3 Numerical treatment

3.1 Advanced Solver for the Direct Problem

Replacing the displacements $\mathbf{u}$ by the approximate FEM-solution $\mathbf{u_h}$ the solving of Eq. (1) reduces to the solving of the huge linear system of equations

$$K \cdot \underline{\mathbf{u}} = \underline{b} \ . \qquad (3)$$

Due to complexity and robustness reasons in the solution process of (3) we need

- iterative Multigrid/Multilevel solvers with adaptive grid refinement, which
- find automatically (also unexpected) areas of interest due to the
- accuracy of derived values (σ) at near-by singularities.

These requirements are met by software developed at our institute in the past years, coded in C++, see NETGEN [1], FEPP [2]. The control of the adaptive FEM-grid refinement on each level k is done by an a posteriori error estimator for the error of the solution ${\mathbf{u_h}}^k$, i.e., $\tilde{z}_h^k \approx z_h^k := |{\mathbf{u_h}}^k - \mathbf{u_h}^*|$ where ${\mathbf{u_h}}^*$ denotes the f.e. interpolation of the exact solution $\underline{\mathbf{u}}$ of system (3).
The numerical examples for the solution of the direct problem, i.e., solving the plain stress state equations, reveals that uniform refinement of the grid immediately leads to huge requirements on storage space and consequently to enormous CPU-consumption.

3.2 Shape optimization

The variables are arranged in groups of discrete and continuous variables. Mathematically, our optimization problem is of the form

$$\begin{array}{ll} \text{minimize} & f(x_I, x_C) \\ & \text{with respect to } x = (x_I, x_C) \\ \text{subject to} & \underline{x_I} \leq x_I \leq \overline{x_I} \\ & \underline{x_C} \leq x_C \leq \overline{x_C} \\ & x_{I,k} \in I\!N \ , \ k = \overline{1, D_I} \\ \exists m \in I\!N_0 & x_{I,k} = \underline{x_{I,k}} + m s_k \ , \ k = \overline{1, D_I} \\ & x_{C,k} \in I\!R \ , \ k = \overline{1, D_C} \ . \end{array}$$

s_k is a given integer step size. D_I, and D_C, denotes the dimension of the vector x_I, and x_C, resp. At first we we generate a list of all continuous box constrained optimization problems by totally enumerating all discrete feasible points (in our case there is for the moment only one discrete variable, the number of wholes in the frame). In the second part of the code all continuous problems are treated as follows:
As there are no equality constraints and as the gradients of the inequality constraints are equal to either e_k or $-e_k$, where e_k denotes the k^{th} unit vector, the regularity conditions and hereby the Kuhn-Tucker-Theorem hold.

All continuous variables are scaled, i.e.

$$\tilde{x}_{C,k} := x_{C,k} \quad / \quad \frac{|\underline{x_{C,k}}| + |\overline{x_{C,k}}|}{2}$$

For sake of simplicity we will always use the notation x_C instead of $\tilde{x}_C$. Starting from a feasible point for the continuous problem, which is always known - e. g. the central point of the feasible region that is formed by the box constraints -, we use a Quasi-Newton method which takes advantage of the simple structure of the constraints during generating and solving the corresponding quadratic optimization problems by the active index set strategy. For updating the Quasi-Newton matrix we use a modified BFGS formula. The optimal solution of one of the generated continuous problems is denoted by $x_C^*(x_I)$. After solving all generated continuous problems, the solution of the mixed integer problem is easily found by just by comparing values of the objective already calculated.

4 Application

During testing the above code we realized that there are more requirements to be met by the design of a frame for an injection moulding machine which were not stated in the beginning. Now this requirement on the tensile stress has already been included in the model. During the *automatic* optimization process we achieved temporary frame geometries resulting in very high stresses in single points or areas which would lead to a damage of the machine. To catch such regions without a very fine grid in the whole domain an adaptive solver is strictly recommended - otherwise we may run into non-admissible solutions.

Note, that part of our objective looks like applying a penalty method. In our model these weight factors are used and interpreted as factors of importance, the "penalty parameters" are about of the same magnitude as the coefficients of the elements in the objective. As our penalty parameters do not tend to infinity, as in the penalty method for constrained optimization, but are fixed given weights, we do not have to cope with the problem of ill-conditioning for larger and larger penalty parameters.

5 Numerical examples

We used a SUN-ULTRA 170MHz (9 SPEC fp95) for optimizing the initial geometry from Fig. 1. The mesh generation and solving of one direct problem took us 60 sec We optimized the shape of the frame with respect to the hole in the center, i.e., we had 12 design variables. Our automatic optimization code stopped after 7 hours resulting in the geometry presented in Fig. 2.



Figure 2: 9th adaptive grid of the optimized shape (3167 elements).

We were able to reduce the mass of the original frame by 5 % that has already been produced for several years. Additionally, a smaller weight $w_{\alpha,s}$ in the soft limit for the angle would result in a bigger decrease of mass. The choice of that weight is still in discussion.

	orig.geom.	opt.geom.
mass	100 %	95 %
$\max \sigma/\sigma_{\max}$	70 %	69 %
$\max \tau/\tau_{\max}$	101 %	100 %
$\alpha/\alpha_{\text{soft}}$	92 %	100 %
$\alpha/\alpha_{\max}$	80 %	88 %

Table 1: Mass reduction and fulfilling of constraints in per cent..

Using advanced mathematical techniques in the solving of the direct problem opens the gate to fast 2D optimization. Transferring these advanced techniques also in the optimization seems to be a promising way for handling 3D optimization problems in future.

Acknowledgment

We would like to thank our colleague Joachim Schöberl for the assistance in adapting the code FEPP to our needs and Michael Bauer from ENGEL Maschinenbau for stimulating discussions.

References

[1] Schöberl, J.: NETGEN: Technical Report No 95-3, Institut für Mathematik, Johannes Kepler Universität Linz, 1995

[2] Schöberl, J.: FEPP:
`www.numa.uni-linz.ac.at/projects/doc/`

Gundolf Haase and Ewald H. Lindner
Institut für Analysis und Numerik
Abteilung für Numerische Mathematik und Optimierung
Johannes Kepler Universität Linz
Altenbergerstr. 69
A-4040 Linz, Austria